

STANDARD HOISTWAY PLAN

NOTE: ALL DIMENSIONS ARE APPROXIMATE

OVERSIZE CAB OPTION ASSUMED

 DRAWN:
 CHECKED:
 DATE:
 REVISION

 G.P.
 F.P.
 4/17/18
 NEW DRAWING

NOTES:

- 1 IF PLATFORM SIZE IS REDUCED, THEN THE BLOCKING IS TO BE POSITIONED SUCH THAT IT IS CENTERED ON THE PLATFORM.

 (PLATFORM DEPTH / 2) + 2" = CENTERLINE OF RAIL BLOCKING OFF OF INSIDE FRONT WALL. (MIN. 23-1/2" DIMENSION)
- (2) CAR TO WALL (CTW) DIMENSION IS 3-1/2" MIN.
- (3) HOISTWAY DOORS AND FRAMES TO BE INSTALLED IN A 2" x 4" WALL CONSTRUCTION OR RECESSED INTO A DEEPER WALL CONSTRUCTION TO EQUATE TO A 2" x 4" WALL. THIS IS REQUIRED TO COMPLY WITH 3" x 5" RULE.
- (4) HOISTWAY DOORS TO BE SOLID CORE (BY OTHERS.)
- (5) CLEAR CAB DIMENSIONS BASED ON A 3/4" FLAT WALL CAB DESIGN. PICTURE FRAME AND FRAME / PANEL CABS REDUCE CLEAR INSIDE WIDTH BY 1-1/2" AND CLEAR INSIDE DEPTH BY 3/4".
- (6) MIN. CLEARANCE TO ALLOW FOR MOTOR/ BRAKE/ GEARBOX



20 RESIDENTIAL DRIVE CRAWFORDVILLE, FL 32327

ResidentialElevators.com

JOB NAME

950#, LH RAIL, IN-LINE OPENING, ACCORDION GATE, 15 SQ. FT.

DRAWING NUMBER

1-800-832-2004

HYD HP2 A 15 60 x 60

THE INFORMATION CONTAINED HEREIN IS SOLELY OWNED BY RESIDENTIAL ELEVATORS, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT WRITTEN PERMISSION FROM RESIDENTIAL ELEVATORS. INC. IS STRICTLY PROHIBITED.